



POWER PROTECTION

Selectric RCD Units

Selectric Active9 Protection Units •



Introduction



The Selectric RCD ranges have been manufactured for the ever demanding modern requirements of today's environment.

Fantastically designed with a compact design and built using the highest level

of quality components, the Selectric and RCD ranges brings you safety, protection and durability!

Manufactured to the latest British and European standards and backed with a 5 year no quibble manufacturer's guarantee, this range is not only stylish but also very durable and long lasting!

Contents

	Page
Selectric RCD Protection Units	47



Features & Benefits

- Gives Additional protection against electrical shocks and risk of fire



- Ideal for home or building site applications




- Trip indication by illuminated mechanical trip indicator



- Test button for safety check



- Compliant with the latest British and European standards & CE approved and marked where applicable



- 5 years no quibble manufacturer's guarantee



Technical Information

Specifications & Features

Flush RCD Protected Sockets & Fused Connection Units

Dimensions

86mmx86mm (1 gang)

146mmx86mm (2 gang)

Supplied with fixing screws:

60.3mm (1 gang)

120.6mm (2 gang)

Metalclad RCD Protected Sockets

Dimensions

86.7mmx86.7mmx44mm (1 gang)

143.9mmx86.7mmx44mm (2 gang)

Selectric RCD Switch Sockets

- Gives Additional protection against electric shocks and fire
- Automatically disconnects live and neutral connections, leaving earth connection intact
- With an on/off switch for extra safety and convenience
- Tripping current: 30mA
- Tripping time: <30ms
- With test button for safety check
- 250V~, 13A, Max. 3000W
- Active/Latching

Selectric "Active" RCD Protected Sockets



SP-RCD2GS
RCD Protected Twin Switched Socket

Features:

- Socket outlets to BS7288
- Double pole switching
- Terminals suitable for up to 3x2.5mm² or 2x4.0mm² conductors
- Tripping current: 30mA
- Tripping time: <30ms
- Automatically disconnect live and neutral connections, leaving earth connection intact
- Non-latching



SP-RCD1GS
RCD Protected Single Switched Socket

Features:

- Socket outlets to BS7288
- Double pole switching
- Terminals suitable for up to 3x2.5mm² or 2x4.0mm² conductors
- Tripping current: 30mA
- Tripping time: <30ms
- Automatically disconnect live and neutral connections, leaving earth connection intact
- Non-latching



Selectric RCD Units

Code No.	Description
SP-RCD1GS	RCD Protected Single Switched Socket
SP-RCD2GS	RCD Protected Twin Switched Socket