



Code	PUSHGLO-15
Description	IP65 pressed steel GU10 240V shower downlighter (fixed head)
Cutout Size & Void	Cut out size: 70mm diameter • Min. ceiling void depth - 120mm
Range	Selectric PushGlo Fire and Acoustic Protected Die Cast and Pressed Steel Downlighters
Colour	White
Material	Iron body & pressed steel bezel
Included	Instructions
Inner Carton Quantity	1
Weight	0.255kg
Inner Carton Weight	0.31kg
Outer Carton Quantity	20
Outer Carton Weight	6.2kg
Warranty	3 Years
Barcode	5025117018613
Commodity Code	9405100000
Standards	EN 55015:2013+A1:2015, EN 61547:2009, EN 61000-3-2:2014 EN 61000-3-3:2013 Fire test: BS 476-21:1987 IEC 60529:1989+A1:1999+A2:2013
Notes	<ul style="list-style-type: none"> • Replace failed lamps immediately • Luminaire suitable for 30, 60 & 90 minutes fire rated timber ceilings & suspended ceilings • Max lamp wattage: 50W • Voltage: 240V



Lamp Wattage	Max 50 Watt
Lamp Position	Fixed
Input	220V-240V
Hertz	50Hz
Operating Temp	-20°C-40°C
Protection Class / IP Rating	IP65
Built-in/Flush Mounting?	Yes
Beam Angle	120°
Bezel Type	Twist & Lock