



<b>Code</b>	PUSHGLO-2
<b>Description</b>	IP20 die-cast GU10 240V downlighter (fixed head)
<b>Cutout Size &amp; Void</b>	Cut out size: 75mm diameter • min. ceiling void depth - 120mm
<b>Range</b>	Selectric PushGlo Fire and Acoustic Protected Die Cast and Pressed Steel Downlighters
<b>Colour</b>	Polished chrome
<b>Material</b>	Iron body & die-cast aluminium bezel
<b>Included</b>	Instructions
<b>Inner Carton Quantity</b>	1
<b>Weight</b>	0.247kg
<b>Inner Carton Weight</b>	0.3kg
<b>Outer Carton Quantity</b>	20
<b>Outer Carton Weight</b>	6kg
<b>Warranty</b>	3 Years
<b>Barcode</b>	5025117018477
<b>Commodity Code</b>	9405100000
<b>Standards</b>	EN 55015:2013+A1:2015, EN 61547:2009, EN 61000-3-2:2014 EN 61000-3-3:2013 Fire test: BS 476-21:1987
<b>Notes</b>	<ul style="list-style-type: none"> <li>• Replace failed lamps immediately</li> <li>• Luminaire suitable for 30, 60 &amp; 90 minutes fire rated timber ceilings &amp; suspended ceilings</li> <li>• Max lamp wattage: 50W • Voltage: 240V</li> </ul>



<b>Lamp Wattage</b>	Max 50 Watt
<b>Lamp Position</b>	Fixed
<b>Input</b>	220V-240V
<b>Hertz</b>	50Hz
<b>Operating Temp</b>	-20°C-40°C
<b>Protection Class / IP Rating</b>	IP20
<b>Built-in/Flush Mounting?</b>	Yes
<b>Beam Angle</b>	120°
<b>Bezel Type</b>	Twist & Lock