



<b>Code</b>	PUSHGLO-5
<b>Description</b>	IP20 die-cast GU10 240V downlighter (30° tilting head)
<b>Cutout Size &amp; Void</b>	Cut out size: 84mm diameter • Min. ceiling void depth - 120mm
<b>Range</b>	Selectric PushGlo Fire and Acoustic Protected Die Cast and Pressed Steel Downlighters
<b>Colour</b>	Polished chrome
<b>Material</b>	Iron body & die-cast aluminium bezel
<b>Included</b>	Instructions
<b>Inner Carton Quantity</b>	1
<b>Weight</b>	0.322kg
<b>Inner Carton Weight</b>	0.37kg
<b>Outer Carton Quantity</b>	20
<b>Outer Carton Weight</b>	7.4kg
<b>Warranty</b>	3 Years
<b>Barcode</b>	5025117018507
<b>Commodity Code</b>	9405100000
<b>Standards</b>	EN 55015:2013+A1:2015, EN 61547:2009, EN 61000-3-2:2014 EN 61000-3-3:2013 Fire test: BS 476-21:1987
<b>Notes</b>	<ul style="list-style-type: none"> <li>• Replace failed lamps immediately</li> <li>• Luminaire suitable for 30, 60 &amp; 90 minutes fire rated timber ceilings &amp; suspended ceilings</li> <li>• Max lamp wattage: 50W • Voltage: 240V</li> </ul>



Lamp Wattage	Max 50 Watt
Lamp Position	30° Tilt
Input	220V-240V
Hertz	50Hz
Operating Temp	-20°C-40°C
Protection Class / IP Rating	IP20
Built-in/Flush Mounting?	Yes
Beam Angle	120°
Bezel Type	Twist & Lock